Serial No. 10/840,205 Filed: 05/06/2004 Inventor: Banas, et al. Attorney Docket: 6006-157 Customer No. 29,335

This Claim Listing replaces all prior versions of claim listings in the application.

## **Claim Listing:**

What is claimed is:

- 1. (Previously Amended) An implantable medical graft, comprising:
  - a. a generally tubular body member comprising a film selected from the group consisting of metallic and pseudometallic materials and having a luminal wall surface, an abluminal wall surface and a thickness intermediate the luminal wall surface and the abluminal wall surface; and
    b. at least a portion of the body member having a plurality of continuous circumferential undulations, with peaks and valleys, formed in each of the luminal wall and abluminal wall surfaces of the body member.
- 2. (Previously Amended) The implantable medical graft according to Claim 1, further comprising a plurality of microperforations passing through the thickness of the body member and communicating between the luminal surface and the abluminal surface.
- 3. (Original) The implantable medical graft according to Claim 1, wherein the film is made of a metallic material selected from the group consisting of titanium, vanadium, aluminum, nickel, tantalum, zirconium, chromium, silver, gold, silicon, magnesium, niobium, scandium, platinum, cobalt, palladium, manganese, molybdenum and alloys thereof.
- 4. (Original) The implantable medical graft according to Claim 2, further comprising at least one of a plurality of non-undulated circumferential regions of the body member.

12168 -2-

Serial No. 10/840,205 Filed: 05/06/2004

Inventor: Banas, et al. Attorney Docket: 6006-157

Customer No. 29,335

5. (Original) The implantable medical graft according to Claim 4, further comprising at least one of a plurality of suturing openings passing through the wall thickness of the at least one of a plurality of non-undulated regions of the body member.

- 6. (Original) The implantable medical graft according to Claim 4, wherein the wall thickness of the undulating regions is less than the wall thickness of the non-undulating regions.
- 7. (Original) The implantable medical graft according to Claim 6, wherein the thickness of the undulating regions is between about  $3-7 \mu m$  and the wall thickness of the non-undulating regions is between about  $10-20 \mu m$ .
- 8. (Original) The implantable medical graft according to Claim 7, wherein the at least a portion of a non-undulating region further comprises at least one of a plurality of suturing openings passing through the wall thickness.
- 9. (Original) The implantable medical graft according to Claim 8, wherein the at least one of a plurality of suturing openings further comprises a generally cruciform-shaped slot pattern.
- 10. (Original) The implantable medical graft according to Claim 8, wherein the at least one of a plurality of suturing openings further comprises a generally Y-shaped slot pattern.
- 11. (Original) The implantable medical graft according to Claim 4, further comprising at least one of a plurality of radially projecting barb members.

12168 -3-

Serial No. 10/840,205 Filed: 05/06/2004 Inventor: Banas, et al. Attorney Docket: 6006-157

Customer No. 29,335

12. (Original) The implantable medical graft according to Claim 4, further comprising at least one of a plurality of suture members integrally extending along a longitudinal axis of the body member.

- 13. (Previously Amended) A method of making an implantable medical graft comprising the steps of:
  - a. providing a generally cylindrical substrate having a plurality of circumferentially extending continuous undulations with peaks and valleys, patterned along at least a portion of a longitudinal axis of the generally cylindrical substrate;
  - b. vacuum depositing a graft-forming material onto the generally cylindrical substrate; and
  - c. releasing the deposited graft-forming material from the substrate.
- 14. (Original) The method according to Claim 13, wherein the graft-forming material is selected from the group consisting of biocompatible metals and pseudometals.
- 15. (Original) The method according to Claim 13, further comprising the step of forming a plurality of microperforations passing through the thickness of the deposited graft-forming material.
- 16. (Original) The method according to Claim 13, further comprising the step of forming at least one of a plurality of suturing openings through the wall thickness of at least one non-undulating region of the deposited graft-forming material.

12168 -4-